

D71 PLUS Dual 7" Rack Mount Monitor

Your complete live production, broadcast monitoring solution for anywhere



2x7"
Screen



FHD
FULL HD
1920X1200



3G
SDI
3G-SDI
In & Out



4K
HDMI
4K HDMI
In & Out



3D
LUT
Custom
3D-LUT



Scope
Analysis



Ethernet
Control




AI
Metal
Housing



>> KEY FEATURES

- 2x7 Inch 1920x1200 full HD IPS screen
- Intuitive buttons + new menu interface, convenient to operation
- 3RU rack mount design, easy to mount on TV wall or broadcast truck
- Upload custom 3D-LUT, preview film look
- With Waveform, Vector scope, RGB Histogram, Focus Assist, Monochrome etc. functions, help you accurately exposure and focus every shot
- Connect to Ethernet remotely adjust the monitor via software
- Front panel built-in 3 colors TALLY indicator, enhance shooting cooperation

>> USE PROFESSIONAL REC.709 COLOR CALIBRATION STANDARD



>> SMARTER TOOLS FOR ABSOLUTE PRECISION



Waveform



Vector



Histogram



RGB Histogram



Embedded Audio



Focus Peaking




Zoom



Zebra




Safe Frames



Etc.

>> USB UPGRADE/ LUT FILE IMPORTING




>> DC 12V, XLR CONNECTOR FLEXIBLE POWER SUPPLY








>> PARAMETER

Description	Dual 7" 3RU Broadcast SDI/HDMI Rack Mount Monitor
Model	D71 PLUS
Screen size	7"x2
Resolution	1920x1200 pixel
Dot pitch	0.07875 (W) x 0.07875 (H) mm
Aspect Ratio	16:10
Brightness	450cd/m2
Contrast	1100:1
Backlight	LED
Viewing Angle	80°/80°(L/R) 80°/80°(U/D)
Inputs	HDMI, 3G/HD/SD-SDI, Audio(L/R),Video
Outputs	HDMI, 3G/HD/SD-SDI, Video, 3.5mm Audio Jack
Control Inputs	Ethernet
SDI Support Format	720p (60/59.94/50/30/29/25/24/23.98) 1080i (60/59.94/50) 1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)
HDMI Support Format	480i/576i/480p/576p 1080i (60/59.94/50) 720p (60/59.94/50/30/29.97/25/24/23.98) 1080p (60/59.94/50/30/29.97/25/24/23.98) 4K 3840×2160p (30/29.97/25/24/23.98 Hz), 4096×2160p (24Hz)
Power Consumption	≤21W
Input Voltage	DC 9V~24V
Operating Temperature	- 10°C ~ 60°C
Storage Temperature	- 30°C ~ 70°C
Install Way	Rack Mount
Unit Size	482.6Lx132Hx30.5D mm
Unit Weight	1890g

>> STRUCTURE



>> PACKING LIST

 <p>Monitor</p>	 <p>Power Adapter</p>	 <p>Tally Kit</p>	 <p>Mini USB to USB Cable</p>	 <p>User Manual</p>
---	--	--	--	--



Zhangzhou Seetec Optoelectronics Technology Co., Ltd

E-mail: sales@feelworld.cn

Tel: +86-596-2182566

Website: www.feelworld.com.cn

Fax: +86-596-2672617

www.seetec.com.cn