

T230 Specification

Picture:



Input Signal:

75 Ohm Digital TV Antenna Input

Receive Frequency: TV 48.25 ~ 863.25 MHz

Full compliance with DVB-T: EN 300 744

2K to 32K FFT Size

Punctured Codes: 1/2, 2/3, 3/4, 4/5, 5/6 and 7/8

DVB-T2: EN 302 755(V1.1.1, V1.2.1, V1.3.1)

Bandwidth: 1.7/5/6/7/8/10MHz

FFT mode: 1K 2K 4K 8K 16K 32K

Guard interval: 1/128 1/32 1/16 1/8 1/4 19/128 19/256

Modulation: BPSK QPSK 16-QAM 64-QAM

Pilot pattern: PP1-PP8

APPR: L1&P2 L1&ACE L1&TR L1, ACE&P2

Code Rate: 1/2 2/3 3/4 4/5 5/6

FEC: LDPC 16K/64K

De-Multiplexing

Max No. Section filtering: 32PIDS

Engine: Software

Stream capture: PES & TS

Decoder

Video: mpg-II Main Profile & Main

Level/H.264/H.265 HEVC

Audio: mpg-II Audio Layer I & II/AAC

Resolution

1080P/1080i/720P/720i

Function:

Advanced TV Application – Watch DVB-T2/T/C TV on PC
Rewind and Fast Forward live TV shows with Always Time Shifting recording.
Electronic Program Guide (EPG) and Supporting HDTV Receiving
Automatic Station Searching
Create favorite stations for convenient listening
Digital Personal Video Recording
Schedule TV recording and save directly to your PC's Hard Drive
High sensitivity under low signal broad casting area

Software Requirement:

HiDTV
Total Media3.5
TotalPlayer

Driver requirement:

Support Windows XP/Vista/7/8/10 OS
Name in Device Manager: DVB-T/T2 USB Stick
Support Linux OS
Support Android OS

Accessories:

T230 USB Dongle
DVB-T Antenna
Remote Cable
Quick Installation Guide

C4i Consultants for Industry

ul. Batalionu Platerówek 3 (bud. B-7, piętro 1)
03-308 Warszawa, Poland
Email: biuro@c4i.com.pl
Telefon: +48 22 398-33-42, +48 22 390-62-36
Kom. +48 515-590-370, +48 790 400 142
poniedziałek – piątek: 9.00-17.30